



## **DESIGNED & ASSEMBLED IN THE USA**

## RUGGED & DURABLE

LONG LIFE: Hydro-Gear's HGM-H family of motors has been designed to provide years of heavy-duty operation supported by knowledgeable application engineers.

SUPERIOR PERFORMANCE: With a large bearing capacity the HGM-H will handle your heavier loads and perform consistently.

SEAMLESS POWER: The HGM-H motors contain high-performing and durable piston drive elements that provide customers with quiet operation and smooth power output.

SPECIFICATIONS		
Geometric Displacement	14.93 in <sup>3</sup> /rev [244.7 cc/rev]	17.84 in³/rev [292.3 cc/rev]
Maximum Speed Continuous Intermittent <sup>1</sup>	210 rpm 250 rpm	185 rpm 210 rpm
Maximum Torque <sup>3</sup> Continuous Intermittent <sup>1</sup> Peak <sup>2</sup>	2700 in-lbf [305 Nm] 4400 in-lbf [497 Nm] 6200 in-lbf [700 Nm]	3200 in-lbf [362 Nm] 5400 in-lbf [610 Nm] 7600 in-lbf [859 Nm]

Intermittent operation: the permissible values may occur for max. 10% of every minute.
 Peak load: the permissible values may occur for max. 1% of every minute.
 70 SUS oil at 210°F at 15gpm and 1000psi and 10gpm at 3000psi.

Specifications subject to change without notice

